

**CALYPSO Filter Grade P**

For coarse pre-filtration, particle removal down to 3 micron

Model	m ³ /h	Connection	Weight	Width	Height	Price	Spare-	Price
		R	KG	mm	mm	€	element	€
P 10	39	1/2"	1,4	87	209	95	EP 10	30
P 15	57	1/2"	1,4	87	209	105	EP 15	33
P 20	79	1/2"	1,4	87	209	117	EP 20	37
P 30	118	3/4"	1,7	87	279	133	EP 30	47
P 55	198	1"	4,2	130	315	207	EP 55	63
P 95	342	1 1/2"	4,8	130	415	237	EP 95	77
P 150	540	1 1/2"	5,6	130	515	266	EP 150	99
P 220	799	1 1/2"	8,4	130	715	397	EP 220	125
P 290	1047	2"	11,4	164	823	541	EP 290	163
P 430	1569	2 1/2"	13	164	1073	665	EP 430	209
P 625	2250	3"	20	250	1052	1,378	EP 625	271
P 775	2797	3"	27,5	250	1202	1,477	EP 775	356

CALYPSO Filter Grade UFor general filtration, particle removal down to 1.0 micron,
oil removal down to 0.1 mg/m³ at 20 deg C

Model	m ³ /h	Connector	Weight	Width	Height	Price	Spare-	Price
		R	KG	mm	mm	€	element	€
U 10	39	1/2"	1,4	87	209	95	EU 10	30
U 15	57	1/2"	1,4	87	209	105	EU 15	33
U 20	79	1/2"	1,4	87	209	117	EU 20	37
U 30	118	3/4"	1,7	87	279	133	EU 30	47
U 55	198	1"	4,2	130	315	207	EU 55	63
U 95	342	1 1/2"	4,8	130	415	237	EU 95	77
U 150	540	1 1/2"	5,6	130	515	266	EU 150	99
U 220	799	1 1/2"	8,4	130	715	397	EU 220	125
U 290	1047	2"	11,4	164	823	541	EU 290	163
U 430	1569	2 1/2"	13	164	1073	665	EU 430	209
U 625	2250	3"	20	250	1052	1,378	EU 625	271
U 775	2797	3"	27,5	250	1202	1,477	EU 775	356

CALYPSO Filter Grade CFor oil vapour and odour removal (activated carbon)
oil removal down to 0.003 mg/m³ at 20 deg C
applicable in oil lubricated compressors in conjunction with filter grade H

Model	m ³ /h	Connection	Weight	Width	Height	Price	Spare-	Price
		R	KG	mm	mm	€	element	€
C 10	39	1/2"	1,4	87	209	95	EC 10	30
C 15	57	1/2"	1,4	87	209	105	EC 15	33
C 20	79	1/2"	1,4	87	209	117	EC 20	37
C 30	118	3/4"	1,7	87	279	133	EC 30	47
C 55	198	1"	4,2	130	315	207	EC 55	63
C 95	342	1 1/2"	4,8	130	415	237	EC 95	77
C 150	540	1 1/2"	5,6	130	515	266	EC 150	99
C 220	799	1 1/2"	8,4	130	715	397	EC 220	125
C 290	1047	2"	11,4	164	823	541	EC 290	163
C 430	1569	2 1/2"	13	164	1073	665	EC 430	209
C 625	2250	3"	20	250	1052	1,378	EC 625	271

Prices for filters include internal automatic drain, stage C without Calypso Filter model 10 to 30 with differential slide indicator Calypso Filter model 55 to 775 with differential pressure gauge

Calypso Filters comply to the European Pressure Equipment Directive, PED 97/23/EC
Max. operating pressure 16 bar g
Max. operating temperature 60° C